



Weight: 20.6 kg

Pos	Stk	Tekst	Tegn. nr.
1	1	PRESSURE REGULATOR R2000SB	
2	1		
3	1	PRESSURE REGULATOR RP3000HAB	
4	2	90° ELBOW SS	
5	1	∅5 SST-PIPE, L = 320 MM	
6	2	NIPPLE 1/4", SS	
7	1	BLEEDER 7050,1B	
8	1	GAUGE, 0-15 BAR	
9	1	GAUGE, 0-400 BAR	
10	1	T-JOINT 1/4" SS	



Model	P.E. I.P.	P.U. O.P.	Flow	Gauges	
				In	Out
	(bar)	(bar)	(Nm ³ /H)		
	370	0,3 – 8	1200 - 3000	0 – 400 bar	0 – 15 bar
	370	8 – 11	3000 - 4200	0 – 400 bar	0 – 25 bar

Pilot regulator:

Body	: Brass
Moving parts, springs and bolts	: Stainless steel / brass
Gaskets	: NBR, Teflon, Nylon
Pressure range inlet	: 0-370 bar
Pressure range outlet	: 0-15 bar depending on pilot pressure
Temperature arrange ambient	: -20°C - +80°C
Media	: Inert gas

OPTIONAL EQUIPMENT:

Pilot pressure control regulator	: R2000SB2 inlet pressure 370 bar outlet 0-11 bar
Gauges	: Depending on pressure range
Sequence / stop system	: 3/2 valve man. override 31619NAM Eexd versions available

For ordering regulators in SS 316	: Order RP33000 HAB
Pilot regulator in SS 316	: Order R32000SB2